US 20240213858A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0213858 A1**

YOSHIMI (43) **Pub. Date: Jun. 27, 2024**

(54) **METHOD FOR MANUFACTURING DRIVE DEVICE, AND DRIVE DEVICE**

(71) Applicant: **DENSO CORPORATION**, Kariya-city (JP)

(72) Inventor: **TOMOAKI YOSHIMI**, Kariya-city (JP)

(21) Appl. No.: **18/601,768**

(22) Filed: **Mar. 11, 2024**

Related U.S. Application Data

(63) Continuation of application No. PCT/JP2022/033452, filed on Sep. 6, 2022.

(30) **Foreign Application Priority Data**

Sep. 14, 2021 (JP) 2021-149768

Publication Classification

(51) **Int. Cl.**

H02K 11/33	(2016.01)
H02K 5/22	(2006.01)
H02K 15/00	(2006.01)

(52) **U.S. Cl.**

CPC ***H02K 11/33*** (2016.01); ***H02K 5/225*** (2013.01); ***H02K 15/00*** (2013.01); *H02K 2211/03* (2013.01)

(57) **ABSTRACT**

One end portion of each connector terminal is connected to an end circuit board of an end circuit board assembly. In a first process, a generic circuit board assembly is assembled to a motor frame. In a second process, the end circuit board assembly is assembled to the generic circuit board assembly. In a third process, the other end portion of each connector terminal of the end circuit board assembly is exposed in a mating bore of a corresponding connector, and a connector housing is assembled. The third process is carried out such that a load, which is generated when the other end portion of each connector terminal is exposed in the mating bore of the corresponding connector in the third process, is smaller than a load, which is generated in the first process, and a load, which is generated in the second process.