(54) **IMAGE DECODING METHOD USING RESIDUAL INFORMATION IN IMAGE CODING SYSTEM, AND DEVICE FOR SAME**

(71) Applicant: **LG Electronics Inc.**, Seoul (KR)

(72) Inventors: **Jungah CHOI**, Seoul (KR); **Jaehyun LIM**, Seoul (KR); **Jin HEO**, Seoul (KR); **Sunmi YOO**, Seoul (KR); **Ling LI**, Seoul (KR); **Jangwon CHOI**, Seoul (KR); **Seunghwan KIM**, Seoul (KR)

(21) Appl. No.: **18/126,143**

(22) Filed: **Mar. 24, 2023**

Related U.S. Application Data

(63) Continuation of application No. 17/732,087, filed on Apr. 28, 2022, now Pat. No. 11,647,202, which is a continuation of application No. 17/373,114, filed on Jul. 12, 2021, now Pat. No. 11,350,101, which is a continuation of application No. PCT/KR2020/000621, filed on Jan. 13, 2020.

(60) Provisional application No. 62/791,747, filed on Jan. 12, 2019.

Publication Classification

(51) **Int. Cl.**
H04N 19/132	(2006.01)
H04N 19/105	(2006.01)
H04N 19/176	(2006.01)
H04N 19/18	(2006.01)
H04N 19/46	(2006.01)
H04N 19/70	(2006.01)
H04N 19/88	(2006.01)

(52) **U.S. Cl.**
CPC *H04N 19/132* (2014.11); *H04N 19/105* (2014.11); *H04N 19/176* (2014.11); *H04N 19/18* (2014.11); *H04N 19/46* (2014.11); *H04N 19/70* (2014.11); *H04N 19/88* (2014.11)

(57) **ABSTRACT**

An image decoding method performed by a decoding device, according to the present document, comprises the steps of: receiving a bitstream including residual information of a current block; deriving a specific number of context-encoding bins for context syntax elements for a current sub-block of the current block; decoding the context syntax elements for the current sub-block included in the residual information on the basis of the specific number; deriving transform coefficients for the current sub-block on the basis of the decoded context syntax elements; deriving residual samples for the current block on the basis of the transform coefficients; and generating a reconstructed picture on the basis of the residual samples.