US 20220360180A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2022/0360180 A1**

KAWAMURA et al. (43) **Pub. Date: Nov. 10, 2022**

(54) **ISOLATED DC-DC CONVERTER**

(71) Applicants: **AutoNetworks Technologies, Ltd.**, Yokkaichi-shi, Mie (JP); **Sumitomo Wiring Systems, Ltd.**, Yokkaichi-shi, Mie (JP); **Sumitomo Electric Industries, Ltd.**, Osaka-shi, Osaka (JP)

(72) Inventors: **Ibuki KAWAMURA**, Yokkaichi-shi, Mie (JP); **Takumi UEMURA**, Yokkaichi-shi, Mie (JP)

(21) Appl. No.: **17/619,709**

(22) PCT Filed: **Jun. 3, 2020**

(86) PCT No.: **PCT/JP2020/021979**

§ 371 (c)(1),
(2) Date: **Dec. 16, 2021**

(30) **Foreign Application Priority Data**

Jun. 18, 2019 (JP) 2019-112480
Mar. 11, 2020 (JP) 2020-041443

Publication Classification

(51) **Int. Cl.**
H02M 3/335 (2006.01)
H02M 1/32 (2006.01)
H02M 1/00 (2006.01)

(52) **U.S. Cl.**
CPC ***H02M 3/33573*** (2021.05); ***H02M 1/32*** (2013.01); ***H02M 1/0009*** (2021.05)

(57) **ABSTRACT**

An isolated DC-DC converter includes a transformer, a full-bridge switching circuit, a protective circuit, a control unit, an inductor, and an output circuit. The isolated DC-DC converter includes a first voltage detection unit that detects a voltage value between a first conductive path and a second conductive path, and a first current detection unit that detects a current value of the inductor. The control unit determines at least one of a first dead time and a second dead time on the basis of the voltage value detected by the first voltage detection unit and the current value detected by the first current detection unit, using a method that increases the dead time as the voltage value increases and reduces the dead time as the current value increases.