



US 20240237394A9

(19) **United States**
(12) **Patent Application Publication**
UEDA

(10) **Pub. No.: US 2024/0237394 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **DISPLAY UNIT, METHOD OF
MANUFACTURING DISPLAY UNIT, AND
ELECTRONIC APPARATUS**

Mar. 19, 2017, now Pat. No. 10,290,832, filed as
application No. PCT/JP2015/076244 on Sep. 16,
2015.

(71) Applicant: **SONY CORPORATION**, Tokyo (JP)

(30) **Foreign Application Priority Data**

(72) Inventor: **Daisuke UEDA**, Tokyo (JP)

Oct. 9, 2014 (JP) 2014-208116

(21) Appl. No.: **18/535,809**

Publication Classification

(22) Filed: **Dec. 11, 2023**

Prior Publication Data

(15) Correction of US 2024/0138182 A1 Apr. 25, 2024
See (22) Filed.
See (30) Foreign Application Priority Data.

(51) **Int. Cl.**
H10K 50/856 (2006.01)
H10K 50/824 (2006.01)
H10K 59/122 (2006.01)
H10K 71/00 (2006.01)
(52) **U.S. Cl.**
CPC *H10K 50/856* (2023.02); *H10K 50/824*
(2023.02); *H10K 59/122* (2023.02); *H10K*
71/00 (2023.02); *H10K 59/38* (2023.02)

(65) US 2024/0138182 A1 Apr. 25, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/988,124, filed on
Nov. 16, 2022, now Pat. No. 11,871,611, which is a
continuation of application No. 17/038,855, filed on
Sep. 30, 2020, now Pat. No. 11,563,198, which is a
continuation of application No. 16/682,135, filed on
Nov. 13, 2019, now Pat. No. 10,826,023, which is a
continuation of application No. 16/369,307, filed on
Mar. 29, 2019, now Pat. No. 10,497,903, which is a
continuation of application No. 15/512,572, filed on

(57)

ABSTRACT

A display unit includes a plurality of pixels, a reflector layer,
and an auxiliary electrode. Each of the plurality of pixels has
a first electrode, an organic layer, and a second electrode in
this order. The organic layer and the second electrode are
provided on the first electrode. The organic layer includes a
light-emitting layer. The reflector layer has a light-reflecting
surface around each of the pixels. The auxiliary electrode is
provided on the reflector layer and is projected from an
upper end of the light-reflecting surface. The auxiliary
electrode has a portion which is exposed from the organic
layer, and the exposed portion is covered with the second
electrode.

