

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213347 A1 Lee et al.

Jun. 27, 2024 (43) **Pub. Date:**

(54) NANOSHEET FIELD-EFFECT TRANSISTOR DEVICE AND METHOD OF FORMING

(71) Applicant: Taiwan Semiconductor

Manufacturing Co., Ltd., Hsinchu

(TW)

(72) Inventors: Hsin-Yi Lee, Hsinchu (TW); Weng

Chang, Hsinchu (TW); Chi On Chui,

Hsinchu (TW)

(21) Appl. No.: 18/598,934

(22) Filed: Mar. 7, 2024

Related U.S. Application Data

- (63) Continuation of application No. 17/577,169, filed on Jan. 17, 2022, now Pat. No. 11,935,937, which is a continuation of application No. 16/904,751, filed on Jun. 18, 2020, now Pat. No. 11,227,931.
- (60) Provisional application No. 62/955,166, filed on Dec. 30, 2019.

Publication Classification

(51) Int. Cl. H01L 29/49 (2006.01)H01L 21/02 (2006.01)

H01L 21/28	(2006.01)
H01L 29/06	(2006.01)
H01L 29/423	(2006.01)
H01L 29/66	(2006.01)
H01L 29/786	(2006.01)

(52) U.S. Cl.

CPC H01L 29/4908 (2013.01); H01L 21/02603 (2013.01); H01L 21/28088 (2013.01); H01L 29/0673 (2013.01); H01L 29/42392 (2013.01); H01L 29/4966 (2013.01); H01L 29/66545 (2013.01); H01L 29/66742 (2013.01); H01L **29/78696** (2013.01)

(57)**ABSTRACT**

A semiconductor device includes a fin protruding above a substrate; source/drain regions over the fin; nanosheets between the source/drain regions; and a gate structure over the fin and between the source/drain regions. The gate structure includes: a gate dielectric material around each of the nanosheets; a first liner material around the gate dielectric material; a work function material around the first liner material; a second liner material around the work function material; and a gate electrode material around at least portions of the second liner material.

