



US 20240213211A1

(19) **United States**

(12) **Patent Application Publication**  
**MORI**

(10) **Pub. No.: US 2024/0213211 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **STORAGE CONTAINER, PROCESSING APPARATUS, BONDING APPARATUS, PROCESSING METHOD, AND BONDING METHOD**

**B65D 43/02** (2006.01)

**B65D 55/02** (2006.01)

(52) **U.S. CL.**

**CPC** ..... **H01L 24/80** (2013.01); **B65D 25/10** (2013.01); **B65D 43/0202** (2013.01); **B65D 55/02** (2013.01); **B65D 2251/0018** (2013.01); **B65D 2251/0081** (2013.01); **H01L 2224/80009** (2013.01); **H01L 2224/80895** (2013.01); **H01L 2224/80896** (2013.01)

(71) Applicant: **CANON KABUSHIKI KAISHA**,  
Tokyo (JP)

(72) Inventor: **KENICHIRO MORI**, Tochigi (JP)

(21) Appl. No.: **18/532,064**

(22) Filed: **Dec. 7, 2023**

(57)

**ABSTRACT**

(30) **Foreign Application Priority Data**

Dec. 21, 2022 (JP) ..... 2022-204637

**Publication Classification**

(51) **Int. Cl.**

**H01L 23/00** (2006.01)

**B65D 25/10** (2006.01)

A storage container for storing a die includes a main body including a first through hole and a second through hole, a first lid that is attachable to the main body to cover the first through hole, and a second lid that is attachable to the main body to cover the second through hole. The die is removed/inserted from/into the main body via the first through hole, and the second through hole is configured to process the die via the second through hole.

