



(19) **United States**

(12) **Patent Application Publication**

Cho et al.

(10) **Pub. No.: US 2024/0215388 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE**

Publication Classification

(71) Applicant: **LG DISPLAY CO., LTD.**, Seoul (KR)

(72) Inventors: **WooChan Cho**, Paju si (KR); **ChulHo Kim**, Seo gu (KR); **JungSik Jo**, Goyang si (KR); **Kyu-Hwang Lee**, Paju si (KR); **Hyunjin Kim**, Goyang si (KR)

(73) Assignee: **LG DISPLAY CO., LTD.**, Seoul (KR)

(51) **Int. Cl.**
H10K 59/80 (2006.01)

(52) **U.S. Cl.**
CPC **H10K 59/872** (2023.02); **H10K 59/873** (2023.02); **H10K 59/131** (2023.02)

(21) Appl. No.: **18/451,245**

(22) Filed: **Aug. 17, 2023**

(30) **Foreign Application Priority Data**
Dec. 22, 2022 (KR) 10-2022-0181405

(57) **ABSTRACT**
A display device includes a substrate including an active area, a hole area disposed within the active area and having a through hole disposed therein, and a disconnection area surrounding the hole area; and a plurality of disconnection structures disposed on the substrate in the disconnection area, wherein each of the plurality of disconnection structures includes, a lower layer, an intermediate layer disposed on the lower layer and having a width smaller than that of the lower layer, and an upper layer disposed on the intermediate layer and having a width greater than that of the intermediate layer, thereby penetration of moisture or oxygen from the through hole into the active area is minimized.

