



US 20240179936A1

(19) **United States**

(12) **Patent Application Publication**

HAN et al.

(10) **Pub. No.: US 2024/0179936 A1**

(43) **Pub. Date: May 30, 2024**

(54) **LIGHT EMITTING ELEMENT, DISPLAY DEVICE INCLUDING SAME, AND MANUFACTURING METHOD OF LIGHT EMITTING ELEMENT**

(71) Applicants: **Samsung Display Co., Ltd.**, Yongin-si (KR); **Hongik University Industry-Academia Cooperation Foundation**, Seoul (KR)

(72) Inventors: **Chang Yeol HAN**, Yongin-si (KR); **Heesun YANG**, Seoul (KR); **Suk-Young YOON**, Seoul (KR)

(73) Assignees: **Samsung Display Co., Ltd.**, Yongin-si (KR); **Hongik University Industry-Academia Cooperation Foundation**, Seoul (KR)

(21) Appl. No.: **18/353,507**

(22) Filed: **Jul. 17, 2023**

(30) **Foreign Application Priority Data**

Nov. 24, 2022 (KR) 10-2022-0159318

Publication Classification

(51) **Int. Cl.**
H10K 50/16 (2006.01)
H10K 50/115 (2006.01)
H10K 59/12 (2006.01)
H10K 59/35 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 50/16** (2023.02); **H10K 50/115** (2023.02); **H10K 59/1201** (2023.02); **H10K 59/35** (2023.02)

(57) **ABSTRACT**

Embodiments provide a light emitting element that includes a first electrode, a second electrode disposed on the first electrode, a light emitting layer disposed between the first electrode and the second electrode and including a quantum dot, a hole transport region disposed between the first electrode and the light emitting layer, and an electron transport layer disposed between the light emitting layer and the second electrode, wherein the electron transport layer includes an electron transport material, and the electron transport material includes a metal oxide particle, and a bicarbonate coupled to a surface of the metal oxide particle.

