

# (19) United States

# (12) Patent Application Publication (10) Pub. No.: US 2023/0231303 A1 PARK et al.

## Jul. 20, 2023 (43) **Pub. Date:**

## WEARABLE ELECTRONIC DEVICE INCLUDING ANTENNA

(71) Applicant: SAMSUNG ELECTRONICS CO., LTD., Suwon-si (KR)

Inventors: Sungkoo PARK, Suwon-si (KR); Kyoungmok KIM, Suwon-si (KR); Seunghwan KIM, Suwon-si (KR); Jonghoon KIM, Suwon-si (KR); Jiyeon YUN, Suwon-si (KR); Jaeho LIM,

Suwon-si (KR); Jaebong CHUN,

Suwon-si (KR)

(21) Appl. No.: 18/118,352

(22)Filed: Mar. 7, 2023

### Related U.S. Application Data

(63) Continuation of application No. PCT/KR2023/ 000572, filed on Jan. 12, 2023.

#### (30)Foreign Application Priority Data

Jan. 12, 2022	(KR)	10-2022-0004665
Mar. 29, 2022	(KR)	10-2022-0038468
Jan. 12, 2023	(KR)	10-2023-0004713

#### **Publication Classification**

(51) Int. Cl. H01Q 1/27 (2006.01) $H01\widetilde{Q}$   $\overline{1/48}$ (2006.01) (52) U.S. Cl. CPC ...... *H01Q 1/273* (2013.01); H01Q 1/48 (2013.01)

#### (57)**ABSTRACT**

An example wearable electronic device may include: a bridge; a first rim disposed in a first direction of the bridge, and a second rim disposed in a second direction of the bridge, the second direction being opposite to the first direction; and a first temple configured to be folded or unfolded with respect to the first rim using a first hinge part, and a second temple configured to be folded or unfolded with respect to the second rim using a second hinge part, wherein the first temple includes: a first printed circuit board on which a wireless communication circuit is disposed and a ground area is partially formed; a non-conductive area formed on a part of the ground area; a feeder wire disposed across the non-conductive area, and having a first end electrically connected to the wireless communication circuit using a signal path and a second end disposed adjacent to the ground area; a feeder point formed adjacent to the second end of the feeder wire and electrically connected to the feeder wire; and a first electronic component electrically connected to a part of the ground area, electrically connected to the feeder point, using a first conductive connection member, wherein the part of the ground area and at least a part of the first electronic component may be utilized as antennas.

