



US 20240215279A1

(19) **United States**

(12) **Patent Application Publication**

MANAGAKI

(10) **Pub. No.: US 2024/0215279 A1**

(43) **Pub. Date:**

Jun. 27, 2024

(54) **DISPLAY DEVICE**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventor: **Nobuto MANAGAKI**, Tokyo (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(21) Appl. No.: **18/391,722**

(22) Filed: **Dec. 21, 2023**

(30) **Foreign Application Priority Data**

Dec. 26, 2022 (JP) 2022-208363

(51) **Int. Cl.**

H10K 50/11

(2006.01)

H10K 50/16

(2006.01)

H10K 50/165

(2006.01)

(52) **U.S. Cl.**

CPC *H10K 50/11* (2023.02); *H10K 50/165* (2023.02); *H10K 50/166* (2023.02)

(57) **ABSTRACT**

According to one embodiment, a display device has such configuration that an electron transport layer includes a high-concentration layer and a low-concentration layer, the high-concentration layer is adjacent to an interface with the electron injection layer, the concentration of Liq contained in the high-concentration layer is 70% or more and 90% or less, the concentration of Liq contained in the low-concentration layer is 10% or more and 50% or less, and the thickness of the high-concentration layer is 5% or more and 15% or less of the thickness of the electron transport layer.