



US 20240180015A1

(19) **United States**

(12) **Patent Application Publication**  
**PARK et al.**

(10) **Pub. No.: US 2024/0180015 A1**

(43) **Pub. Date: May 30, 2024**

(54) **METHOD OF MANUFACTURING FLEXIBLE TRANSPARENT ELECTRODES, FLEXIBLE TRANSPARENT ELECTRODES MANUFACTURED BY THE METHOD, AND ELECTROFIELD LIGHT EMITTING DEVICE HAVING THE FLEXIBLE TRANSPARENT ELECTRODE**

(71) Applicant: **University-Industry Foundation(UIF), Yonsei University, Seoul (KR)**

(72) Inventors: **Cheolmin PARK, Seoul (KR); Wei JIANG, Seoul (KR); Seokyeong LEE, Seoul (KR)**

(73) Assignee: **University-Industry Foundation(UIF), Yonsei University, Seoul (KR)**

(21) Appl. No.: **18/475,404**

(22) Filed: **Sep. 27, 2023**

(30) **Foreign Application Priority Data**

Sep. 27, 2022 (KR) ..... 10-2022-0122692

**Publication Classification**

(51) **Int. Cl.**

**H10K 71/60** (2006.01)

**H01B 1/22** (2006.01)

**H10K 50/81** (2006.01)

**H10K 50/828** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H10K 71/60** (2023.02); **H01B 1/22** (2013.01); **H10K 50/81** (2023.02); **H10K 50/828** (2023.02)

(57)

**ABSTRACT**

Disclosed is a method for manufacturing a flexible transparent electrode. The method for manufacturing the flexible transparent electrode includes a first step of forming a transparent polymer layer on a substrate; a second step of spray-coating silver nanowires (AgNWs) on the transparent polymer layer; a third step of spray-coating MXene flakes on the transparent polymer layer having the silver nanowires coated thereon; and a fourth step of pressing and, at the same time, heat-treating an upper surface of the transparent polymer layer on which the silver nanowires and the MXene flakes have been coated.

