



US 20240213981A1

(19) **United States**(12) **Patent Application Publication**
AGARWAL et al.(10) **Pub. No.: US 2024/0213981 A1**(43) **Pub. Date: Jun. 27, 2024**(54) **MULTI-CHANNEL MULTIPLEXER****H03K 17/00** (2006.01)(71) Applicant: **Texas Instruments Incorporated,**
Dallas, TX (US)**H03K 17/10** (2006.01)(52) **U.S. Cl.**(72) Inventors: **Nitin AGARWAL**, Bengaluru (IN);
Kunal Suresh KARANJKAR,
Bengaluru (IN); **Venkata Ramanan R**,
Bengaluru (IN)CPC **H03K 17/693** (2013.01); **H03F 3/72**
(2013.01); **H03K 17/005** (2013.01); **H03K**
17/102 (2013.01)(21) Appl. No.: **18/599,361**

(57)

ABSTRACT(22) Filed: **Mar. 8, 2024****Related U.S. Application Data**(63) Continuation of application No. 17/169,638, filed on
Feb. 8, 2021, now Pat. No. 11,955,964, which is a
continuation of application No. 16/700,444, filed on
Dec. 2, 2019, now Pat. No. 10,917,090.**Publication Classification**(51) **Int. Cl.****H03K 17/693** (2006.01)**H03F 3/72** (2006.01)

A circuit includes a first switch assembly having a first input node and a first output node, and a second switch assembly having a second input node and a second output node. The circuit further includes a third switch assembly an operational amplifier, and a buffer. The third switch assembly has a third input node and a third output node. The third input node is coupled to the second output node, and the third output node is coupled to the first output node. The buffer has a buffer input and a buffer output. The buffer input is coupled to an input stage of the operational amplifier. The buffer output is coupled to the third switch assembly.

