



US 20220354029A1

(19) **United States**(12) **Patent Application Publication**  
**HAYASHI**(10) **Pub. No.: US 2022/0354029 A1**(43) **Pub. Date: Nov. 3, 2022**(54) **ELECTRONIC EQUIPMENT****H05K 5/06** (2006.01)**H05K 5/03** (2006.01)(71) Applicant: **Susa Inc.**, Tokyo (JP)(52) **U.S. Cl.**(72) Inventor: **Yukinori HAYASHI**, Tokyo (JP)CPC ..... **H05K 7/20963** (2013.01); **H05K 5/0017**  
(2013.01); **H05K 5/06** (2013.01); **H05K**  
**5/0008** (2013.01); **H05K 5/03** (2013.01)(21) Appl. No.: **17/728,475**(22) Filed: **Apr. 25, 2022**

(57)

**ABSTRACT**(30) **Foreign Application Priority Data**

Apr. 28, 2021 (JP) ..... 2021-075675

Nov. 11, 2021 (JP) ..... 2021-184272

**Publication Classification**(51) **Int. Cl.****H05K 7/20** (2006.01)**H05K 5/00** (2006.01)

Electronic equipment allowed to endure repetitive severe environmental change in a sterilizing treatment using an autoclave is provided. A tablet terminal (electronic equipment) **106** includes: an enclosure **10**; a substrate **30** arranged in an internal space of the enclosure **10**; an electronic circuit component **40** mounted on the substrate **30**; a (first) heat insulating layer **50** formed along the enclosure **10**; and a (first) heat release mechanism **70** allowed to discharge heat from an internal space of the heat insulating layer **50** to outside of the enclosure **10**.

