



US 20240213491A1

(19) **United States**

(12) **Patent Application Publication**
Wang et al.

(10) **Pub. No.: US 2024/0213491 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **POROUS MATERIAL AND PREPARATION METHOD THEREOF, CURRENT COLLECTOR, SECONDARY BATTERY, AND APPARATUS**

(71) Applicant: **CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED**, Ningde (CN)

(72) Inventors: **Manman Wang**, Ningde (CN);
Xiaoming Ge, Ningde (CN)

(21) Appl. No.: **18/430,630**

(22) Filed: **Feb. 1, 2024**

Related U.S. Application Data

(63) Continuation of application No. PCT/CN2022/088398, filed on Apr. 22, 2022.

Publication Classification

(51) **Int. Cl.**
H01M 4/66 (2006.01)
H01M 4/02 (2006.01)
H01M 4/80 (2006.01)
(52) **U.S. Cl.**
CPC *H01M 4/661* (2013.01); *H01M 4/80* (2013.01); *H01M 2004/021* (2013.01); *H01M 2220/20* (2013.01)

(57) **ABSTRACT**

This application provides a porous material and a preparation method thereof, a current collector, a secondary battery, and an apparatus. The porous material has pores of a first pore size and pores of a second pore size. The second pore size is m nanometers, and $10 < m < 400$; and the first pore size is n micrometers, and $0.5 \leq n \leq 20$. An apparent volume of the porous material is V , a total pore volume of the pores of the second pore size is V_2 , a total pore volume of the pores of the first pore size is V_1 , and the porous material satisfies the following relationships: $(V_1 + V_2)/V = 20\% - 90\%$, $V_2/V = 15\% - 70\%$, and $V_1/V = 5\% - 70\%$.

