



US 20240237478A9

(19) **United States**
(12) **Patent Application Publication**
He et al.

(10) **Pub. No.: US 2024/0237478 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **DISPLAY PANEL AND DISPLAY DEVICE**

Prior Publication Data

(71) Applicants: **TCL CHINA STAR
OPTOELECTRONICS
TECHNOLOGY CO., LTD.,**
Shenzhen, Guangdong (CN);
**HUIZHOU CHINA STAR
OPTOELECTRONICS DISPLAY
CO., LTD.,** Huizhou, Guangdong (CN)

(15) Correction of US 2024/0138230 A1 Apr. 25, 2024
See (22) PCT Filed
See (86) PCT No.

(65) US 2024/0138230 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Mar. 11, 2022 (CN) 202210239257.7

Publication Classification

(72) Inventors: **Chao He**, Shenzhen, Guangdong (CN);
Shijian Qin, Shenzhen, Guangdong
(CN)

(51) **Int. Cl.**
H10K 59/80 (2006.01)

(73) Assignees: **TCL CHINA STAR
OPTOELECTRONICS
TECHNOLOGY CO., LTD.,**
Shenzhen, Guangdong (CN);
**HUIZHOU CHINA STAR
OPTOELECTRONICS DISPLAY
CO., LTD.,** Huizhou, Guangdong (CN)

(52) **U.S. Cl.**
CPC **H10K 59/80522** (2023.02)

(57) **ABSTRACT**

The present application discloses a display panel and a display device. The display panel includes a plurality of sub-pixels, a cathode, and an auxiliary electrode disposed in a layer different from the cathode. An extension length of the sub-pixel along the first direction is smaller than an extension length of the sub-pixel along the second direction, and the second direction intersects the first direction. The cathode contact hole is located between at least two adjacent rows of the sub-pixels, or the cathode contact hole is located between at least two adjacent columns of sub-pixels and extends along the first direction.

(21) Appl. No.: **17/755,001**
(22) PCT Filed: **Mar. 25, 2022**
(86) PCT No.: **PCT/CN2022/082987**
§ 371 (c)(1),
(2) Date: **Apr. 19, 2022**

