



US 20240237311A1

(19) **United States**(12) **Patent Application Publication**
LI et al.(10) **Pub. No.: US 2024/0237311 A1**(43) **Pub. Date: Jul. 11, 2024**(54) **HEAT DISSIPATION SYSTEM AND
SOLID-STATE TRANSFORMER POWER
APPARATUS**(71) Applicant: **DELTA ELECTRONICS, INC.**,
Taoyuan City (TW)(72) Inventors: **Sheng-Hua LI**, Taoyuan City (TW);
Wei-Chi LEE, Taoyuan City (TW);
Ming-Chen YEN, Taoyuan City (TW);
Chun-Han LIN, Taoyuan City (TW)(21) Appl. No.: **18/502,930**(22) Filed: **Nov. 6, 2023****Related U.S. Application Data**(60) Provisional application No. 63/437,449, filed on Jan.
6, 2023.(30) **Foreign Application Priority Data**

Jun. 15, 2023 (CN) 202310712663.5

Publication Classification(51) **Int. Cl.**
H05K 7/20 (2006.01)(52) **U.S. Cl.**
CPC **H05K 7/20927** (2013.01); **H05K 7/20272**
(2013.01); **H05K 7/20945** (2013.01)(57) **ABSTRACT**

A heat dissipation is used to dissipate heat for a power module of an AC-to-DC conversion module. The heat dissipation system includes a chiller, a heat exchanger, a first circulation pipeline, a second circulation pipeline, a first throttle valve, and a control module. The chiller, the heat exchanger, and the first circulation pipeline form a first circulation loop to circulate a low-temperature coolant. The second circulation pipeline is disposed on one side of the power module to form a second circulation loop, and absorbs a heat source generated by the power module by circulating a high-temperature coolant. The control module opens the first throttle valve to introduce the low-temperature coolant into the second circulation loop based on a temperature of the high-temperature coolant being greater than a temperature threshold so as to control the temperature to be less than or equal to the temperature threshold.

