



US 20230232668A1

(19) **United States**

(12) **Patent Application Publication**
LEE et al.

(10) **Pub. No.: US 2023/0232668 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **ELECTRONIC PANEL AND ELECTRONIC
DEVICE HAVING THE SAME**

H10K 50/844 (2006.01)

H10K 59/40 (2006.01)

H10K 59/131 (2006.01)

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si
(KR)

(52) **U.S. Cl.**

CPC **H10K 59/124** (2023.02); **G06F 3/041**

(2013.01); **H10K 50/844** (2023.02); **H10K**

59/40 (2023.02); **H10K 59/131** (2023.02)

(72) Inventors: **Minji LEE**, Asan-si (KR);
HYUNGJUN AN, Cheonan-si (KR);
Jeongoh JIN, Hwaseong-si (KR)

(21) Appl. No.: **18/151,461**

(22) Filed: **Jan. 8, 2023**

Related U.S. Application Data

(63) Continuation of application No. 16/905,831, filed on
Jun. 18, 2020, now Pat. No. 11,574,971.

(30) **Foreign Application Priority Data**

Jul. 5, 2019 (KR) 10-2019-0081492

Publication Classification

(51) **Int. Cl.**

H10K 59/124 (2006.01)

G06F 3/041 (2006.01)

(57)

ABSTRACT

An electronic panel including a display panel and an input sensor which includes a base layer, a first sensing electrode, a first signal line electrically connected to the first sensing electrode, a first insulating layer overlapping the first sensing electrode, a second sensing electrode, a second signal line electrically connected to the second sensing electrode, and a second insulating layer overlapping the second sensing electrode, in which the first insulating layer includes an open edge that defines an open area, the open area exposes a portion of a first surface of the base layer and a portion of the first signal line in a plan view, and the first insulating layer has a first thickness at a first point spaced apart from the open edge and a second thickness greater than the first thickness at a second point disposed farther away from the open edge than the first point.

