



US 20240237448A1

(19) **United States**

(12) **Patent Application Publication**
XU et al.

(10) **Pub. No.: US 2024/0237448 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY PANEL AND METHOD FOR
FABRICATING SAME**

H10K 59/121 (2006.01)

H10K 59/122 (2006.01)

H10K 59/124 (2006.01)

(71) Applicant: **SHENZHEN CHINA STAR
OPTOELECTRONICS
SEMICONDUCTOR DISPLAY
TECHNOLOGY CO., LTD.**,
Guangdong (CN)

(52) **U.S. Cl.**

CPC *H10K 59/1315* (2023.02); *H10K 59/1201*
(2023.02); *H10K 59/1213* (2023.02); *H10K*
59/122 (2023.02); *H10K 59/124* (2023.02)

(72) Inventors: **Qiankun XU**, Shenzhen (CN); **Xingyu
ZHOU**, Shenzhen (CN)

(57)

ABSTRACT

(21) Appl. No.: **17/610,509**

(22) PCT Filed: **Sep. 29, 2021**

(86) PCT No.: **PCT/CN2021/121598**

§ 371 (c)(1),

(2) Date: **Nov. 11, 2021**

(30) **Foreign Application Priority Data**

Sep. 17, 2021 (CN) 202111094996.3

Publication Classification

(51) **Int. Cl.**

H10K 59/131 (2006.01)

H10K 59/12 (2006.01)

A display panel includes a light-emitting area and a cathode overlapping area, and further includes a first metal layer including a first wire located in the cathode overlapping area, a second metal layer disposed above the first metal layer and including a second wire located in the cathode overlapping area, a third metal layer disposed above the second metal layer and including an extension wire located in the cathode overlapping area, and a light-emitting device disposed above the second metal layer and located in the light-emitting area. The light-emitting device includes an anode layer, an organic functional layer, and a cathode layer in sequence. The cathode layer extends from the light-emitting area to the cathode overlapping area and is connected to the extension wire.

