

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0222967 A1 TANABE et al.

Jul. 4, 2024 (43) **Pub. Date:**

(54) POWER SUPPLY SYSTEM

Applicant: DENSO CORPORATION, Kariya-city

Inventors: Yasuhito TANABE, Kariya-city (JP); Dachao WANG, Kariya-city (JP)

Assignee: **DENSO CORPORATION**, Kariya-city

(21)Appl. No.: 18/606,183

Filed: Mar. 15, 2024 (22)

Related U.S. Application Data

(63) Continuation of application No. PCT/JP2022/ 032787, filed on Aug. 31, 2022.

(30)Foreign Application Priority Data

Sep. 17, 2021 (JP) 2021-152527

Publication Classification

(51) Int. Cl. H02J 1/08 (2006.01)B60L 50/60 (2006.01)B60L 53/60 (2006.01) H02J 1/10 (2006.01)H02J 7/00 (2006.01)H02J 7/34 (2006.01)

(52) U.S. Cl.

CPC H02J 1/084 (2020.01); H02J 1/082 (2020.01); H02J 1/122 (2020.01); H02J 7/0031 (2013.01); H02J 7/0047 (2013.01); H02J 7/007182 (2020.01); H02J 7/342 (2020.01); H02J 7/345 (2013.01); B60L 50/60 (2019.02); B60L 53/60 (2019.02)

(57)ABSTRACT

A power supply system includes a main relay provided on a high-voltage path between a high-voltage battery and electrical equipment, a charging relay provided on a charging path connected between the main relay and the electrical equipment, and a control device that controls opening and closing of the main relay and the charging relay. The control device, the main relay, and the charging relay operate using electrical power supplied from a low-voltage battery. In a state in which the main relay and the charging relay are closed, the high-voltage battery is charged by charging it with power supplied from a charging device. In addition, the power supply system includes a relay interruption unit that interrupts the charging relay before interrupting the main relay if a voltage reduction abnormality of the low-voltage battery has occurred under a state in which both the main relay and the charging relay are closed.

