



US 20240222977A1

(19) **United States**(12) **Patent Application Publication**
Kobayashi et al.(10) **Pub. No.: US 2024/0222977 A1**(43) **Pub. Date: Jul. 4, 2024**(54) **SMOOTHING-TARGET-VALUE
CALCULATION DEVICE, POWER SUPPLY
SYSTEM, SMOOTHING-TARGET-VALUE
CALCULATION METHOD, AND PROGRAM****Publication Classification**

(51) **Int. Cl.**
H02J 3/32 (2006.01)
G01R 21/00 (2006.01)
H02J 3/46 (2006.01)
H02J 7/35 (2006.01)

(52) **U.S. Cl.**
CPC *H02J 3/32* (2013.01); *G01R 21/00*
(2013.01); *H02J 3/46* (2013.01); *H02J 7/35*
(2013.01); *H02J 2300/24* (2020.01)

(71) Applicant: **MITSUBISHI HEAVY INDUSTRIES,
LTD., Tokyo (JP)**(72) Inventors: **Yu Kobayashi, Tokyo (JP); Yusuke
Yashiro, Tokyo (JP); Masayuki
Hashimoto, Tokyo (JP)**(73) Assignee: **MITSUBISHI HEAVY INDUSTRIES,
LTD., Tokyo (JP)**(21) Appl. No.: **18/558,844**(22) PCT Filed: **Apr. 25, 2022**(86) PCT No.: **PCT/JP2022/018658**

§ 371 (c)(1),

(2) Date: **Nov. 3, 2023**(30) **Foreign Application Priority Data**

Jun. 8, 2021 (JP) 2021-095605

(57) **ABSTRACT**

Provided is a smoothing-target-value calculation device that is capable of calculating a smoothing target value with which it is possible to suppress battery degradation. The present invention provides a smoothing-target-value calculation device that calculates a smoothing target value, which is a target value for the sum of first power generated by a renewable-energy power generation system and second power charged into and discharged from a battery, the smoothing-target-value calculation device including: a predicted-value acquisition unit that acquires a predicted value for the first power; a predicted-value correction unit that corrects the predicted value; and a smoothing-target-value calculation unit that calculates a smoothing target value by smoothing the corrected predicted value.

