



US 20240237456A9

(19) **United States**
(12) **Patent Application Publication**
SONG et al.

(10) **Pub. No.: US 2024/0237456 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **ORGANIC LIGHT-EMITTING DEVICE**

Publication Classification

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si (KR)
(72) Inventors: **Hajin SONG**, Yongin-si (KR); **Jihwan YOON**, Yongin-si (KR); **Sangwoo LEE**, Yongin-si (KR); **Sangwoo PYO**, Yongin-si (KR)

(51) **Int. Cl.**
H10K 59/35 (2006.01)
H10K 50/11 (2006.01)
H10K 50/125 (2006.01)
H10K 50/15 (2006.01)
H10K 50/16 (2006.01)
H10K 59/131 (2006.01)
H10K 71/00 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 59/35** (2023.02); **H10K 50/11** (2023.02); **H10K 50/125** (2023.02); **H10K 50/15** (2023.02); **H10K 50/16** (2023.02); **H10K 59/131** (2023.02); **H10K 71/00** (2023.02); **H10K 50/852** (2023.02)

(21) Appl. No.: **18/400,296**
(22) Filed: **Dec. 29, 2023**

Prior Publication Data

(15) Correction of US 2024/0138221 A1 Apr. 25, 2024
See (30) Foreign Application Priority Data.
(65) US 2024/0138221 A1 Apr. 25, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/154,471, filed on Jan. 13, 2023, now Pat. No. 11,903,288, which is a continuation of application No. 17/201,737, filed on Mar. 15, 2021, now Pat. No. 11,581,371, which is a continuation of application No. 16/852,875, filed on Apr. 20, 2020, now Pat. No. 10,971,554, which is a continuation of application No. 16/432,375, filed on Jun. 5, 2019, now Pat. No. 10,658,432, which is a continuation of application No. 15/870,389, filed on Jan. 12, 2018, now Pat. No. 10,325,960, which is a continuation of application No. 15/141,910, filed on Apr. 29, 2016, now Pat. No. 9,905,616.

Foreign Application Priority Data

Oct. 28, 2015 (KR) 10-2015-0150453

(57) **ABSTRACT**

An organic light-emitting device and display apparatus, the device including a first electrode; a second electrode facing the first electrode; an emission layer between the first and second electrode; a hole control layer between the first electrode and the emission layer; and an electron control layer between the emission layer and the second electrode, wherein the emission layer includes a plurality of sub-emission layers to emit light having different wavelengths, at least portions of the plurality of sub-emission layers do not overlap one another, the plurality of sub-emission layers include: a first sub-emission layer including a first color light-emitting dopant, and a second sub-emission layer including a second color light-emitting dopant, the first and second sub-emission layers each include a hole-transporting and electron-transporting host which form an exciplex, and a triplet energy of the exciplex is equal to or greater than triplet energies of the first and second color light-emitting dopant.

