

# (19) United States

# (12) Patent Application Publication (10) Pub. No.: US 2024/0222976 A1

Jul. 4, 2024 (43) Pub. Date:

## (54) OPTIMAL POWER FLOW-BASED HIERARCHICAL CONTROL METHOD FOR DISTRIBUTED ENERGY STORAGE SYSTEM (ESS)

(71) Applicant: State Grid Hubei Electric Power Research Institute, Wuhan, Hubei

(CN)

(72) Inventors: **Defu Cai**, Wuhan, Hubei (CN); Kunpeng Zhou, Wuhan, Hubei (CN); Zuowei Wang, Wuhan, Hubei (CN); Xiaohui Li, Wuhan, Hubei (CN); Li Wan, Wuhan, Hubei (CN); Haiguang Liu, Wuhan, Hubei (CN); Rusi Chen, Wuhan, Hubei (CN); Wenna Wang, Wuhan, Hubei (CN); Tao Wang, Wuhan, Hubei (CN); Liangyi Zhang, Wuhan, Hubei (CN); Guanqun Sun, Wuhan, Hubei (CN); Erxi Wang,

Wuhan, Hubei (CN)

(21) Appl. No.: 17/923,917

(22) PCT Filed: Sep. 1, 2022

(86) PCT No.: PCT/CN2022/116400

§ 371 (c)(1),

(2) Date: Nov. 8, 2022

#### (30)Foreign Application Priority Data

Mar. 14, 2022 (CN) ...... 202210249224.0

### **Publication Classification**

(51) Int. Cl. H02J 3/28 (2006.01)H02J 3/16 (2006.01)H02J 3/24 (2006.01)

U.S. Cl. CPC **H02J 3/28** (2013.01); **H02J 3/16** (2013.01); H02J 3/241 (2020.01); H02J 2203/10 (2020.01); H02J 2203/20 (2020.01)

#### (57)ABSTRACT

Disclosed is an optimal power flow-based hierarchical control method for a distributed energy storage system (ESS), where the method divides control of an energy storage cluster into three layers, performs primary and secondary control to realize intra-cluster control, and performs tertiary control to realize inter-cluster control. In the primary control, droop coefficients are set to realize intra-cluster basic power distribution. In the secondary control, a frequency/ voltage shift and uneven power distribution that are caused by a droop are compensated for based on a consistency algorithm. In the tertiary control, a central controller is set, a solution of an optimal power flow is calculated and delivered to each cluster as a control signal, and the control signal is tracked in real time through the secondary control and the primary control. The method adjusts a reference voltage of each energy storage cluster without requiring a common bus.

