

US 20240237292A9

## (19) United States

# (12) Patent Application Publication Ohyama et al.

### (10) Pub. No.: US 2024/0237292 A9

# (48) **Pub. Date: Jul. 11, 2024 CORRECTED PUBLICATION**

#### (54) ELECTRONIC APPARATUS

(71) Applicant: Lenovo (Singapore) Pte. Ltd., Singapore (SG)

(72) Inventors: **Atsushi Ohyama**, Kanagawa (JP); **Yusuke Onoue**, Kanagawa (JP);

Akinori Uchino, Kanagawa (JP)

(73) Assignee: Lenovo (Singapore) Pte. Ltd.,

Singapore (SG)

(21) Appl. No.: 18/459,361

(22) Filed: Aug. 31, 2023

#### **Prior Publication Data**

(15) Correction of US 2024/0138116 A1 Apr. 25, 2024See (22) Filed.See (30) Foreign Application Priority Data.

(65) US 2024/0138116 A1 Apr. 25, 2024

(30) Foreign Application Priority Data

Oct. 20, 2022 (JP) ...... 2022-168252

#### **Publication Classification**

(51) Int. Cl. *H05K 7/20* (2006.01)

*G06F 1/20* (2006.01) (52) **U.S. Cl.** 

CPC ....... *H05K 7/20481* (2013.01); *G06F 1/203* (2013.01)

#### (57) ABSTRACT

An electronic apparatus includes a CPU provided in a first chassis and generating heat, a plate-shaped vapor chamber provided in the first chassis and thermally connected to the CPU to radiate heat, and two heat pipes protruding and extending from the vapor chamber at positions separated from each other. A graphite sheet that is thinner than the vapor chamber is thermally connected to the two heat pipes. A battery device having three cells is provided in the first chassis, and the heat pipe extends into a groove portion formed between the cells.



