

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231617 A1 MURAKAMI et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) RELAY METHOD AND RELAY DEVICE

Applicant: Sun Patent Trust, New York, NY (US)

(72) Inventors: Yutaka MURAKAMI, Kanagawa (JP); Tomohiro KIMURA, Osaka (JP); Mikihiro OUCHI, Osaka (JP)

(21) Appl. No.: 18/123,505

(22)Filed: Mar. 20, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/243,988, filed on Apr. 29, 2021, now Pat. No. 11,658,733, which is a continuation of application No. 16/790,358, filed on Feb. 13, 2020, now Pat. No. 11,070,281, which is a continuation of application No. 16/017,244, filed on Jun. 25, 2018, now Pat. No. 10,623,084, which is a continuation of application No. 15/617,550, filed on Jun. 8, 2017, now Pat. No. 10,044,432, which is a continuation of application No. 15/202,924, filed on Jul. 6, 2016, now Pat. No. 9,806,793, which is a continuation of application No. 14/582,610, filed on Dec. 24, 2014, now Pat. No. 9,426,631, which is a continuation of application No. 14/110,783, filed on Oct. 9, 2013, now Pat. No. 8,989,237, filed as application No. PCT/JP2012/002676 on Apr. 18, 2012.

(30)Foreign Application Priority Data

Apr. 19, 2011	(JP)	 2011-093539
Apr. 28, 2011	(JP)	 2011-102099
May 26, 2011	(JP)	 2011-118453

Jun. 24, 2011	(JP)	2011-140747
Sep. 2, 2011	(JP)	2011-192123

Publication Classification

(51)	Int. Cl.	
	H04B 7/155	(2006.01)
	H04L 27/34	(2006.01)
	H04L 25/03	(2006.01)
	H04L 27/26	(2006.01)
	H04B 7/06	(2006.01)
	H04L 5/00	(2006.01)
	H04B 7/0456	(2006.01)
	H04W 4/06	(2006.01)
	H04W 40/22	(2006.01)

(52) U.S. Cl.

CPC H04B 7/15542 (2013.01); H04L 27/34 (2013.01); H04L 25/03171 (2013.01); H04L 27/2614 (2013.01); H04B 7/0604 (2013.01); H04L 25/03949 (2013.01); H04L 5/0053 (2013.01); H04B 7/0456 (2013.01); H04L 25/0391 (2013.01); H04W 4/06 (2013.01); H04W 40/22 (2013.01); H04B 7/0413 (2013.01)

(57)ABSTRACT

Disclosed is a relay method including: receiving, as input, respective reception signals by two receive antennas, the reception signals each including a reception signal resulting from multiplexing respective transmission signals transmitted by two transmission antennas in a first frequency band; performing frequency conversion on the reception signal received by one of the receive antennas so as to obtain a signal of a third frequency band; and performing frequency multiplexing on the signal having the third frequency band and the reception signal received by the other of the receive antennas.



