US 20240244939A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0244939 A1**

SHI et al. (43) **Pub. Date: Jul. 18, 2024**

(54) **DISPLAY APPARATUS, DISPLAY PANEL AND MANUFACTURING METHOD THEREFOR**

(71) Applicants: **Chengdu BOE Optoelectronics Technology Co., Ltd.**, Sichuan (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

(72) Inventors: **Quan SHI**, Beijing (CN); **Bo SHI**, Beijing (CN); **Guanghua XU**, Beijing (CN); **Zeyu LI**, Beijing (CN); **Chi YU**, Beijing (CN); **Haijun QIU**, Beijing (CN); **Ming HU**, Beijing (CN); **Weiyun HUANG**, Beijing (CN); **Xiangdan DONG**, Beijing (CN); **Hui GUAN**, Beijing (CN)

(21) Appl. No.: **18/563,460**

(22) PCT Filed: **Feb. 28, 2022**

(86) PCT No.: **PCT/CN2022/078191**

§ 371 (c)(1),
(2) Date: **Nov. 22, 2023**

Publication Classification

(51) **Int. Cl.**

H10K 59/80	(2006.01)
H10K 59/12	(2006.01)
H10K 59/122	(2006.01)
H10K 59/40	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 59/879*** (2023.02); ***H10K 59/1201*** (2023.02); ***H10K 59/122*** (2023.02); *H10K 59/40* (2023.02)

(57) **ABSTRACT**

A display panel includes a driving backplane, a plurality of light-emitting devices spaced apart at a side of the driving backplane a pixel definition layer located at a same side of the driving backplane as the light-emitting device and provided with a plurality of openings and a lens layer located at a side of the light-emitting device away from the driving backplane. The lens layer includes a separating lens and an intermediate lens, the separating lens is provided with a light-transmitting hole, and the intermediate lens is located within a range surrounded by the light-transmitting hole and is spaced apart from a sidewall of the light-transmitting hole. The display panel further includes a dielectric layer covering the lens layer and filling the light-transmitting hole, and a cover plate located at a side of the dielectric layer away from the driving backplane.