US 20220352729A1

(19) **United States**

(12) **Patent Application Publication**

Suyama et al.

(10) **Pub. No.: US 2022/0352729 A1**

(43) **Pub. Date: Nov. 3, 2022**

(54) **BATTERY PACK, AND ABNORMALITY MONITORING METHOD FOR SAME**

(71) Applicant: **SANYO Electric Co., Ltd.**, Daito-shi, Osaka (JP)

(72) Inventors: **Atsushi Suyama**, Osaka (JP); **Junpei Ito**, Tokyo (JP)

(73) Assignee: **SANYO Electric Co., Ltd.**, Daito-shi, Osaka (JP)

(21) Appl. No.: **17/619,647**

(22) PCT Filed: **Jun. 11, 2020**

(86) PCT No.: **PCT/JP2020/022937**

§ 371 (c)(1),
(2) Date: **Dec. 16, 2021**

(30) **Foreign Application Priority Data**

Jun. 27, 2019 (JP) 2019-119647

Publication Classification

(51) **Int. Cl.**

H02J 7/00	(2006.01)
H02J 7/34	(2006.01)
H01M 10/44	(2006.01)
H01M 10/48	(2006.01)

(52) **U.S. Cl.**

CPC ***H02J 7/0029*** (2013.01); ***H02J 7/0047*** (2013.01); ***H02J 7/0013*** (2013.01); ***H02J 7/342*** (2020.01); ***H02J 7/007*** (2013.01); ***H01M 10/44*** (2013.01); ***H01M 10/486*** (2013.01)

(57) **ABSTRACT**

A battery pack includes a current detector configured to detect a charging current to secondary battery, a drive circuit configured to drives a charge switch based on the charging current detected by the current detector, a charge controller configured to control operation of the charge switch by the drive circuit, a monitoring unit configured to monitor operation of charge controller, and a judging unit configured to instruct, based on the charge controller and the monitoring unit, the charge switch to be able to or unable to operate.