



US 20240215440A1

(19) **United States**(12) **Patent Application Publication**
SHIOMI et al.(10) **Pub. No.: US 2024/0215440 A1**(43) **Pub. Date: Jun. 27, 2024**(54) **ORGANIC ELECTROLUMINESCENT
ELEMENT AND ELECTRONIC DEVICE**(71) Applicant: **IDEMITSU KOSAN CO., LTD.**,
Tokyo (JP)(72) Inventors: **Takushi SHIOMI**, Tokyo (JP); **Hisato
MATSUMOTO**, Tokyo (JP); **Yukitoshi
JINDE**, Tokyo (JP); **Kengo KISHINO**,
Tokyo (JP); **Kazuki TERADA**, Tokyo
(JP); **Keiichi YASUKAWA**, Tokyo (JP);
Toshinari OGIWARA, Tokyo (JP)(73) Assignee: **IDEMITSU KOSAN CO., LTD.**,
Tokyo (JP)(21) Appl. No.: **18/282,302**(22) PCT Filed: **Mar. 14, 2022**(86) PCT No.: **PCT/JP2022/011316**

§ 371 (c)(1),

(2) Date: **Sep. 15, 2023**(30) **Foreign Application Priority Data**

Mar. 15, 2021 (JP) 2021-041802

Publication Classification(51) **Int. Cl.****H10K 85/60** (2006.01)**C07D 495/04** (2006.01)**C07F 5/02** (2006.01)**C09K 11/06** (2006.01)**H10K 50/11** (2006.01)(52) **U.S. Cl.**CPC **H10K 85/657** (2023.02); **C07D 495/04**
(2013.01); **C07F 5/027** (2013.01); **C09K 11/06**
(2013.01); **H10K 85/658** (2023.02); **C09K**
2211/1018 (2013.01); **H10K 50/11** (2023.02)

(57)


ABSTRACT

An organic electroluminescence device includes: an anode; a cathode; and an emitting layer between the anode and the cathode, in which the emitting layer contains a delayed fluorescent compound M2 represented by a formula (2) below and a compound M3 represented by a formula (3) below, and a singlet energy S_1 (M2) of the compound M2 and a singlet energy S_1 (M3) of the compound M3 satisfy a relationship of a numerical formula (Numerical Formula 1) below,


(Numerical Formula 1)

$$S_1(M3) > S_1(M2).$$

(2)



(3)



100

