



(12) **Patent Application Publication**  
**Park**

(43) **Pub. Date:** **Jun. 27, 2024**

<i>H01L 23/552</i>	(2006.01)
<i>H01L 21/48</i>	(2006.01)
<i>H01L 21/56</i>	(2006.01)
<i>H01L 23/00</i>	(2006.01)
<i>H01L 23/053</i>	(2006.01)

CPC ..... *H01L 23/552* (2013.01); *H01L 21/4817*  
(2013.01); *H01L 21/4853* (2013.01); *H01L*  
*21/565* (2013.01); *H01L 23/053* (2013.01);  
*H01L 23/3128* (2013.01); *H01L 23/49838*  
(2013.01); *H01L 24/48* (2013.01); *H01L*  
*25/0657* (2013.01); *H01L 25/105* (2013.01);  
*H01L 25/50* (2013.01); *H01L 2224/48157*  
(2013.01); *H01L 2225/06506* (2013.01); *H01L*  
*2225/0651* (2013.01); *H01L 2225/06537*  
(2013.01); *H01L 2225/06562* (2013.01); *H01L*  
*2225/06586* (2013.01); *H01L 2225/1023*  
(2013.01); *H01L 2225/1058* (2013.01); *H01L*  
*2924/3025* (2013.01)

## ABSTRACT

A method of fabricating a semiconductor package includes mounting at least one semiconductor chip to a package substrate, forming a shielding wall around the at least one semiconductor chip, forming a molded body on the package substrate in a space surrounded by the shielding wall, and forming a shielding cover covering the molding unit and in contact with the shielding wall.

