



US 20220352873A1

(19) **United States**(12) **Patent Application Publication**  
**Garcia et al.**(10) **Pub. No.: US 2022/0352873 A1**(43) **Pub. Date: Nov. 3, 2022**(54) **LOW LOSS TRANSVERSELY-EXCITED  
FILM BULK ACOUSTIC RESONATORS AND  
FILTERS**(71) Applicant: **Resonant Inc.**, Austin, TX (US)(72) Inventors: **Bryant Garcia**, Mississauga (CA);  
**Greg Dyer**, Santa Barbara, CA (US)(21) Appl. No.: **17/855,711**(22) Filed: **Jun. 30, 2022****Related U.S. Application Data**


- (63) Continuation-in-part of application No. 17/555,349, filed on Dec. 17, 2021, which is a continuation-in-part of application No. 17/229,767, filed on Apr. 13, 2021.
- (60) Provisional application No. 63/244,565, filed on Sep. 15, 2021, provisional application No. 63/196,645, filed on Jun. 3, 2021, provisional application No. 63/012,849, filed on Apr. 20, 2020, provisional application No. 63/066,520, filed on Aug. 17, 2020, provisional application No. 63/074,991, filed on Sep. 4, 2020.

**Publication Classification**

- (51) **Int. Cl.**  
*H03H 9/54* (2006.01)  
*H03H 9/13* (2006.01)  
*H03H 9/17* (2006.01)  
*H03H 9/02* (2006.01)
- (52) **U.S. Cl.**  
CPC ..... *H03H 9/54* (2013.01); *H03H 9/13*  
(2013.01); *H03H 9/17* (2013.01); *H03H*  
*9/0211* (2013.01)

(57) **ABSTRACT**

An acoustic resonator device includes a portion of a piezo-electric plate is a diaphragm spanning a cavity in a substrate. A conductor pattern on a surface of the piezoelectric plate includes an interdigital transducer (IDT) with a first busbar, a second busbar, and a plurality of interleaved fingers extending alternately from the first and second busbars, first and second reflector elements proximate and parallel to a first finger of the interleaved fingers, and third and fourth reflector element proximate and parallel to a last finger of the interleaved fingers. Overlapping portions of the interleaved fingers and the first to fourth reflector elements are on the diaphragm.  $pr1$  is a center-to-center distance of the first and second reflector elements and a center-to-center distance of the third and fourth reflector elements,  $p$  is a pitch of the interleaved fingers, and  $1.1p \leq pr1 \leq 1.5p$ .



Notes: Only one of actions 1510A, 1510B, 1510C is performed in each of three variations of the process 1500.