



US 20230232651A1

(19) **United States**

(12) **Patent Application Publication**  
**GAO et al.**

(10) **Pub. No.: US 2023/0232651 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **ORGANIC LIGHT-EMITTING DEVICE,  
LIGHT-EMITTING SUBSTRATE AND  
LIGHT-EMITTING APPARATUS**

*H10K 85/40* (2006.01)

*H10K 50/15* (2006.01)

(52) **U.S. Cl.**

CPC ..... *H10K 50/18* (2023.02); *H10K 85/654*  
(2023.02); *H10K 85/6574* (2023.02); *H10K*  
*85/40* (2023.02); *H10K 85/6576* (2023.02);  
*H10K 85/658* (2023.02); *H10K 85/6572*  
(2023.02); *H10K 50/181* (2023.02); *H10K*  
*50/15* (2023.02); *H10K 2101/30* (2023.02)

(71) Applicant: **BOE TECHNOLOGY GROUP CO.,  
LTD.**, Beijing (CN)

(72) Inventors: **Rongrong GAO**, Beijing (CN); **Lei  
CHEN**, Beijing (CN)

(21) Appl. No.: **17/626,147**

(22) PCT Filed: **Jan. 4, 2021**

(86) PCT No.: **PCT/CN2021/070101**

§ 371 (c)(1),

(2) Date: **Jan. 11, 2022**

**Publication Classification**

(51) **Int. Cl.**

*H10K 50/18* (2006.01)

*H10K 85/60* (2006.01)

(57)

**ABSTRACT**

An organic light-emitting device includes: an anode, an emitting layer, and a cathode that are stacked; a first functional material layer located between the emitting layer and the anode; and a second functional material layer located between the emitting layer and the cathode. Under a same test condition, a hole mobility of a material of the first functional material layer is at least ten times an electron mobility of a material of the second functional material layer.

124b 124c 123 125c 125b

