



US 20240215415A1

(19) **United States**

(12) **Patent Application Publication**
JI et al.

(10) **Pub. No.: US 2024/0215415 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE**

59/40 (2023.02); *H10K 59/873* (2023.02);

H10K 2102/3026 (2023.02)

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(72) Inventors: **MI-RAN JI**, Yongin-si (KR);
Changwook KIM, Yongin-si (KR)

(57)

ABSTRACT

(21) Appl. No.: **18/368,016**

(22) Filed: **Sep. 14, 2023**

(30) **Foreign Application Priority Data**

Dec. 21, 2022 (KR) 10-2022-0180705

Publication Classification

(51) **Int. Cl.**

H10K 59/80 (2006.01)

H10K 59/122 (2006.01)

H10K 59/35 (2006.01)

H10K 59/40 (2006.01)

(52) **U.S. Cl.**

CPC **H10K 59/8792** (2023.02); **H10K 59/122**
(2023.02); **H10K 59/35** (2023.02); **H10K**

Provided is a display device including first light-emitting elements activated in a first operation mode and deactivated in a second operation mode, second light-emitting elements activated in the first and second operation modes, a base substrate including a first region having a first light-emitting region where the first light-emitting elements are disposed and a first non-light-emitting region, and a second region adjacent to the first region and having a second light-emitting region where the second light-emitting elements are disposed and a second non-light-emitting region, an encapsulation layer disposed on the base substrate, a first light-blocking pattern not overlapping the first region and overlapping the second non-light-emitting region, a cover layer covering the first light-blocking pattern, and a second light-blocking pattern disposed on the cover layer and overlapping the first light-blocking pattern, wherein the thickness of the cover layer may be greater than the thickness of the encapsulation layer.

