

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0368149 A1 KATAGIRI et al.

Nov. 17, 2022 (43) **Pub. Date:**

(54) POWER STORAGE DEVICE AND **OPERATION METHOD OF POWER** STORAGE DEVICE

(71) Applicant: SEMICONDUCTOR ENERGY LABORATORY CO., LTD.,

ATSUGI-SHI, KANAGAWA-KEN (JP)

(72) Inventors: Haruki KATAGIRI, Atsugi, Kanagawa

(JP); Kyoichi MUKAO, Odawara, Kanagawa (JP); Motohiro ENDO,

Meguro, Tokyo (JP)

17/771,970 (21) Appl. No.:

(22)PCT Filed: Oct. 19, 2020

(86) PCT No.: PCT/IB2020/059795

§ 371 (c)(1),

(2) Date: Apr. 26, 2022

(30)Foreign Application Priority Data

Nov. 1, 2019 (JP) 2019-200251

Publication Classification

(51) Int. Cl. H02J 7/00 (2006.01)H02J 7/34 (2006.01)

H02M 1/10 (2006.01)

(52)U.S. Cl.

> H02J 7/007182 (2020.01); H02J 7/00714 CPC (2020.01); H02J 7/34 (2013.01); H02M 1/10 (2013.01)

(57)ABSTRACT

Power consumption of a power storage device is reduced. A highly safe power storage device is provided. Safety of a battery monitored by a semiconductor device is improved. Power consumption is reduced; for example, power in a resting state is reduced. Time needed to perform processing for transition from a resting state to a normal state is shortened or energy is reduced. A power storage device includes a battery, a control circuit, and a converter circuit. The converter circuit has a function of supplying a voltage to the battery; and the control circuit has a function of measuring data of a voltage of the battery and a function of retaining the data of the voltage of the battery.

<u>100</u>

