



US 20240179835A1

(19) **United States**

(12) **Patent Application Publication**
HORI

(10) **Pub. No.: US 2024/0179835 A1**

(43) **Pub. Date: May 30, 2024**

(54) **STRETCHABLE DEVICE**

H05K 1/14 (2006.01)

H05K 1/18 (2006.01)

(71) Applicant: **Murata Manufacturing Co., Ltd.**,
Nagaokakyo-shi (JP)

(52) **U.S. Cl.**

CPC **H05K 1/0283** (2013.01); **H05K 1/118**
(2013.01); **H05K 1/144** (2013.01); **H05K**
1/145 (2013.01); **H05K 1/189** (2013.01);
H05K 1/0393 (2013.01)

(72) Inventor: **Nobuyasu HORI**, Nagaokakyo-shi (JP)

(21) Appl. No.: **18/435,032**

(22) Filed: **Feb. 7, 2024**

Related U.S. Application Data

(63) Continuation of application No. PCT/JP22/32254,
filed on Aug. 26, 2022.

Foreign Application Priority Data

Nov. 19, 2021 (JP) 2021-188854

Publication Classification

(51) **Int. Cl.**

H05K 1/02 (2006.01)

H05K 1/03 (2006.01)

H05K 1/11 (2006.01)

(57)

ABSTRACT

A stretchable device that includes: a stretchable first substrate having a first main surface and a second main surface facing each other and extending in a first direction; a stretchable first wiring on the first main surface and extending along the first main surface; a second substrate that has a third main surface and a fourth main surface facing each other; and a second wiring on the third main surface and extending along the third main surface. The first substrate includes a connection region overlapping the second substrate and a non-connection region not overlapping the second substrate when viewed from a direction orthogonal to the first main surface, the stretchable first substrate and the second substrate are connected in the connection region, and the stretchable first substrate has a first hole portion in at least one of the first main surface and the second main surface in the non-connection region.

