



US 20240237318A9

(19) **United States**  
(12) **Patent Application Publication**  
**Krishnan**

(10) **Pub. No.: US 2024/0237318 A9**  
(48) **Pub. Date: Jul. 11, 2024**  
**CORRECTED PUBLICATION**

(54) **CONFIGURABLE FARADAY CAGE**

**Publication Classification**

(71) Applicant: **Ajay Subramaniam Krishnan**, Los Altos, CA (US)

(51) **Int. Cl.**  
**H05K 9/00** (2006.01)  
**H10N 70/20** (2006.01)

(72) Inventor: **Ajay Subramaniam Krishnan**, Los Altos, CA (US)

(52) **U.S. Cl.**  
CPC ..... **H05K 9/0071** (2013.01); **H10N 70/20** (2023.02); **H10N 70/231** (2023.02); **G02F 1/0327** (2013.01); **H05K 9/0081** (2013.01)

(21) Appl. No.: **18/492,687**

(22) Filed: **Oct. 23, 2023**

(57) **ABSTRACT**

**Prior Publication Data**

(15) Correction of US 2024/0138131 A1 Apr. 25, 2024  
See (22) Filed.

A configurable cage of Faraday has a cavity enveloped by a layer of conductive material whose resistance can be modified by an external stimulus. The conductive material may be inside or outside a substrate or may be without a substrate. The layer may be continuous, or applied in a pattern, such as a mesh. The conductive material can be a perovskite or a phase-change memory material, and the external stimulus can be electrical. Various electrical pulses can be used to configure the resistance/conductivity of the material, and therefore the level of shielding from magnetic waves that the Faraday cage provides.

(65) US 2024/0138131 A1 Apr. 25, 2024

**Related U.S. Application Data**

(60) Provisional application No. 63/418,610, filed on Oct. 23, 2022.

