US 20240214047A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0214047 A1**

Ahmed et al. (43) **Pub. Date: Jun. 27, 2024**

(54) **METHODS AND APPARATUSES FOR DETERMINING CHANNEL STATE INFORMATION INTERFERENCE MEASUREMENT RESOURCES FOR INTERFERENCE MEASUREMENT**

(71) Applicant: **Telefonaktiebolaget LM Ericsson (publ)**, Stockholm (SE)

(72) Inventors: **Saad Naveed Ahmed**, Sundbyberg (SE); **Hong Ren**, Kanata (CA); **Wei Wang**, Kanata (CA)

(21) Appl. No.: **18/288,759**

(22) PCT Filed: **Apr. 30, 2021**

(86) PCT No.: **PCT/SE2021/050403**

§ 371 (c)(1),
(2) Date: **Oct. 27, 2023**

Publication Classification

(51) **Int. Cl.**

H04B 7/06	(2006.01)
H04B 17/336	(2006.01)
H04W 72/1273	(2006.01)
H04W 76/40	(2006.01)

(52) **U.S. Cl.**

CPC ***H04B 7/0626*** (2013.01); ***H04B 17/336*** (2015.01); ***H04W 72/1273*** (2013.01); ***H04W 76/40*** (2018.02)

(57) **ABSTRACT**

Embodiments described herein relate to methods and apparatuses for determining channel state information interference measurement, CSI-IM resources for interference measurement in a NR cell, wherein the NR cell is sharing a frequency carrier with a Long Term Evolution, LTE, cell under the control of a LTE base station. A method in an NR base station serving the NR cell comprises: generating a CSI-IM pattern for enabling at least one wireless device to perform interference measurements wherein the CSI-IM pattern comprises at least one CSI-IM resource in an Multicast-Broadcast Single-Frequency Network, MBSFN, slot of the LTE cell and at least one CSI-IM resource in a non-MBSFN slot of the LTE cell; and sending an indication of the CSI-IM pattern to the LTE base station.