US 20230231202A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231202 A1

OUYANG et al. (43) Pub. Date: Jul. 20, 2023

(54) **BATTERY PACK, AND POWER CONSUMING DEVICE THEREOF**

(71) Applicant: **CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED**, Ningde (CN)

(72) Inventors: **Shaocong OUYANG**, Ningde (CN); **Chenghua FU**, Ningde (CN); **Baoyun XU**, Ningde (CN); **Miaomiao DONG**, Ningde (CN); **Yonghuang YE**, Ningde (CN)

(73) Assignee: **CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED**, Ningde (CN)

(21) Appl. No.: **18/118,756**

(22) Filed: **Mar. 8, 2023**

Related U.S. Application Data

(63) Continuation of application No. PCT/CN2021/131490, filed on Nov. 18, 2021.

Publication Classification

(51) **Int. Cl.**

H01M 10/0585	(2006.01)
H01M 50/204	(2006.01)
H01M 4/133	(2006.01)
H01M 10/44	(2006.01)

(52) **U.S. Cl.**

CPC ***H01M 10/0585*** (2013.01); ***H01M 50/204*** (2021.01); ***H01M 4/133*** (2013.01); ***H01M 10/441*** (2013.01); *H01M 2220/20* (2013.01); *H01M 2004/028* (2013.01)

(57) **ABSTRACT**

A battery pack may include a first battery cell type and a second battery cell type, wherein the first battery cell type may include n first battery cells, and the second battery cell type may include m second battery cells, with n and m being each independently selected from an integer of 1 or more, wherein the second battery cell may have a discharge power at −20° C. greater than that of the first battery cell, the difference in discharge power at −20° C. between the second battery cells and the first battery cells being ≥10 W; the percentage by number of the first battery cells in the battery cells comprised in area A may be 20% to 100%, and the percentage by number of the second battery cells in the battery cells comprised in the area B may be 5% to 100%.