



US 20240213512A1

(19) **United States**

(12) **Patent Application Publication**
QI et al.

(10) **Pub. No.: US 2024/0213512 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **STACKING APPARATUS**

Publication Classification

(71) Applicant: **Guangdong Lyric Robot Automation Co., Ltd.**, Guangdong (CN)

(51) **Int. Cl.**
H01M 10/04 (2006.01)

(72) Inventors: **Hong QI**, Guangdong (CN); **Junxiong ZHOU**, Guangdong (CN); **Junjie ZHOU**, Guangdong (CN); **Haisheng CAI**, Guangdong (CN); **Xiaotao XU**, Guangdong (CN); **Yifeng WANG**, Guangdong (CN)

(52) **U.S. Cl.**
CPC **H01M 10/0404** (2013.01)

(73) Assignee: **Guangdong Lyric Robot Automation Co., Ltd.**, Guangdong (CN)

(57) **ABSTRACT**

(21) Appl. No.: **17/908,228**

(22) PCT Filed: **Jul. 8, 2022**

(86) PCT No.: **PCT/CN2022/104658**

§ 371 (c)(1),

(2) Date: **Aug. 30, 2022**

Stacking apparatus includes: a base, a first drive element, and a limiting mechanism, the base is provided with a feeding side and a blanking side; an output end of the first drive element is in connection with the base, and the first drive element is configured for driving the rotation of the base so as to switch between the feeding side and the blanking side; the limiting mechanism is provided on the base, both the feeding side and the blanking side are provided with at least one limiting mechanism, a placement region is formed in the limiting mechanism, the limiting mechanism includes limiting plates arranged to be opposite to each other, the limiting plates are arranged to extend along a vertical direction perpendicular to the base, and at least one of the limiting plates moves relatively or oppositely, so as to adjust the length of the placement region.

(30) **Foreign Application Priority Data**

Jun. 28, 2022 (CN) 202221639589.6

