

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0244908 A1 WEI et al.

Jul. 18, 2024 (43) **Pub. Date:**

(54) FLEXIBLE DISPLAY PANEL, DISPLAY DEVICE AND FORMING METHOD

(71) Applicants: CHENGDU BOE **OPTOELECTRONICS** TECHNOLOGY CO., LTD., Chengdu, Sichuan (CN); BOE TECHNOLOGY **GROUP CO., LTD.**, Beijing (CN)

(72) Inventors: Yulong WEI, Beijing (CN); Xiangdan DONG, Beijing (CN); Jun YAN, Beijing (CN); Mengmeng DU, Beijing (CN)

(73) Assignees: CHENGDU BOE **OPTOELECTRONICS** TECHNOLOGY CO., LTD., Chengdu, Sichuan (CN); BOE TECHNOLOGY **GROUP CO., LTD.**, Beijing (CN)

(21) Appl. No.: 18/619,340

(22) Filed: Mar. 28, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/425,222, filed on Jul. 22, 2021, now Pat. No. 11,974,475, filed as application No. PCT/CN2020/077264 on Feb. 28, 2020.

Publication Classification

(51)	Int. Cl.	
	H10K 59/131	(2023.01)
	H10K 59/122	(2023.01)
	H10K 59/40	(2023.01)
	H10K 77/10	(2023.01)
	G06F 3/041	(2006.01)

(52) U.S. Cl. CPC H10K 59/131 (2023.02); H10K 59/122 (2023.02); H10K 59/40 (2023.02); H10K 77/111 (2023.02); G06F 3/0412 (2013.01)

(57)ABSTRACT

A flexible display panel, a display device and a forming method are provided. The flexible display panel includes a display area and a non-display area, where the non-display area includes a bending sub-area and a binding sub-area, and the bending sub-area is configured to bend the binding sub-area to a side away from the display area, the bending sub-area includes a first organic layer, a second organic layer and a metal wiring layer between the first organic layer and the second organic layer arranged on the substrate, the touch wiring layer is electrically connected to the metal wiring layer; in response to the bending sub-area being in a bending state, a vertical distance from a bending neutral layer of the bending sub-area to the metal wiring layer is smaller than a preset distance.

