

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0232660 A1 Kim et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) **DISPLAY APPARATUS**

(71) Applicant: Samsung Display Co., Ltd., Yongin-si

(72) Inventors: **Kyongjun Kim**, Yongin-si (KR); Yongbin Kim, Yongin-si (KR); Sohyun Shin, Yongin-si (KR); Gunwoo Yang, Yongin-si (KR); Dongjin Lee, Yongin-si (KR); Heejin Jeon, Yongin-si

(KR); Hyunyoung Choi, Yongin-si

(KR)

Appl. No.: 17/891,986 (21)

(22)Filed: Aug. 19, 2022

(30)Foreign Application Priority Data

Jan. 17, 2022 (KR) 10-2022-0006800

Publication Classification

(51) Int. Cl. (2006.01)H01L 27/32 G09G 3/3233 (2006.01)

(52) U.S. Cl.

CPC H01L 27/326 (2013.01); H01L 27/3234 (2013.01); H01L 27/3272 (2013.01); G09G 3/3233 (2013.01); G09G 2300/0852 (2013.01); G09G 2300/0861 (2013.01); G09G 2300/0819 (2013.01); G09G 2300/0426 (2013.01); G09G 2320/0242 (2013.01); G09G 2320/0233 (2013.01)

(57)ABSTRACT

A display apparatus includes a first pixel circuit and a second pixel circuit. The first pixel circuit includes a first driving transistor and a first storage capacitor having a first lower storage electrode connected to a gate of the first driving transistor and a first upper storage electrode overlapping the first lower storage electrode. The second pixel circuit includes a second driving transistor and a second storage capacitor including a second lower storage electrode connected to a gate of the second driving transistor and a second upper storage electrode overlapping the second lower storage electrode. A second overlapping area of the second lower storage electrode and the second upper storage electrode is about twice to about four times a first overlapping area of the first lower storage electrode and the first upper storage electrode.

