US 20240251647A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0251647 A1**

LARGE et al. (43) **Pub. Date: Jul. 25, 2024**

(54) **ACTIVE SLACK MANAGEMENT IN A LAYERED ARTICLE**

(71) Applicant: **Microsoft Technology Licensing, LLC**, Redmond, WA (US)

(72) Inventors: **Timothy Andrew LARGE**, Southwater (GB); **Rajesh Manohar DIGHDE**, Redmond, WA (US)

(73) Assignee: **Microsoft Technology Licensing, LLC**, Redmond, WA (US)

(21) Appl. No.: **18/559,412**

(22) PCT Filed: **May 12, 2022**

(86) PCT No.: **PCT/US2022/072273**

§ 371 (c)(1),
(2) Date: **Nov. 7, 2023**

(30) **Foreign Application Priority Data**

May 19, 2021 (NL) 2028249

Publication Classification

(51) **Int. Cl.**

H10K 59/95	(2006.01)
G02F 1/1333	(2006.01)
H10K 59/10	(2006.01)
H10N 39/00	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 59/95*** (2023.02); ***G02F 1/133305*** (2013.01); ***H10K 59/10*** (2023.02); ***H10N 39/00*** (2023.02)

(57) **ABSTRACT**

A method to reduce slack in a display layer of a flexible electronic-display device comprises arranging the display layer slidably relative to an electrically conductive support layer of the electronic-display device; arranging a dielectric layer between the electrically conductive support layer and an electrically conductive sublayer of the display layer; and charging the electrically conductive sublayer relative to the electrically conductive support layer to operatively urge the display layer toward the electrically conductive support layer.