



US 20240237439A1

(19) **United States**

(12) **Patent Application Publication**  
**CHOI**

(10) **Pub. No.: US 2024/0237439 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY DEVICE AND METHOD OF  
MANUFACTURING THE SAME**

(52) **U.S. Cl.**

CPC ..... *H10K 59/131* (2023.02); *H10K 59/1201*  
(2023.02); *H10K 71/231* (2023.02)

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si  
(KR)

(57)

**ABSTRACT**

(72) Inventor: **JONGHYUN CHOI**, Yongin-si (KR)

A display device includes: a substrate having a transmission area, a display area, and an intermediate area between the transmission and display areas; a first active layer including a first active pattern; a first conductive layer on the first active layer and including a gate electrode overlapping the first active pattern; a second active layer on the first conductive layer and including a second active pattern; a second conductive layer between the first conductive layer and the second active layer; a third conductive layer on the second conductive layer and including a bridge electrode electrically connecting the gate electrode and the second active pattern; a first sub-layer in the intermediate area and on a same layer as the second conductive layer; and a second sub-layer covering an outer surface of the first sub-layer. The first and second sub-layers have connected first and second sub-openings, respectively.

(21) Appl. No.: **18/452,399**

(22) Filed: **Aug. 18, 2023**

(30) **Foreign Application Priority Data**

Jan. 11, 2023 (KR) ..... 10-2023-0003886

**Publication Classification**

(51) **Int. Cl.**

*H10K 59/131* (2006.01)

*H10K 59/12* (2006.01)

*H10K 71/20* (2006.01)

