

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0215414 A1 JOO et al.

Jun. 27, 2024 (43) **Pub. Date:**

(54) DISPLAY APPARATUS AND METHOD OF MANUFACTURING THE SAME

(71) Applicant: SAMSUNG DISPLAY CO., LTD., Yongin-si (KR)

(72) Inventors: Sunkyu JOO, Yongin-si (KR); Sunyoung KWON, Yongin-si (KR); Sangji PARK, Yongin-si (KR); Jaecheol PARK, Yongin-si (KR); Keunchan OH, Yongin-si (KR); Dokyung YOUN, Yongin-si (KR); Songee LEE, Yongin-si (KR); Wooman JI, Yongin-si (KR); Youyoung JIN, Yongin-si (KR); Taehyung HWANG, Yongin-si (KR)

(21) Appl. No.: 18/229,529

Filed: (22)Aug. 2, 2023

(30)

Dec. 23, 2022 (KR) 10-2022-0183074

Foreign Application Priority Data

(51)	Int. Cl.	
, ,	H10K 59/80	(2006.01)
	H10K 59/12	(2006.01)
	H10K 59/122	(2006.01)
	H10K 59/38	(2006.01)

(52) U.S. Cl. CPC H10K 59/8792 (2023.02); H10K 59/1201 (2023.02); H10K 59/122 (2023.02); H10K 59/38 (2023.02)

Publication Classification

(57) ABSTRACT

A display apparatus includes a first substrate, first to third light-emitting elements disposed over the first substrate and each including a first-color emission layer and a secondcolor emission layer, a second substrate disposed over the first substrate, a bank disposed on a lower surface of the second substrate facing the first substrate, where first to third bank openings is defined through the bank to overlap the first to third light-emitting elements, a first to third color filter layers disposed between the bank and the second substrate and overlapping the first to third light-emitting elements, a quantum-dot layer disposed in the third bank opening to overlap the third light-emitting element, and a spacer disposed on a lower surface of the bank facing the first substrate and including a same material as a material of the quantumdot layer.

