



US 20240215405A1

(19) **United States**(12) **Patent Application Publication**  
Seong et al.(10) **Pub. No.: US 2024/0215405 A1**(43) **Pub. Date: Jun. 27, 2024**(54) **DISPLAY APPARATUS****Publication Classification**(71) Applicant: **LG Display Co., Ltd.**, Seoul (KR)(72) Inventors: **Sejong Seong**, Paju-si (KR);  
**KyungMin Kim**, Paju-si (KR); **Hyemin Park**, Paju-si (KR); **SeHong Park**,  
Paju-si (KR); **Wonrae Kim**, Paju-si  
(KR); **Inae Choi**, Paju-si (KR);  
**SeoHyun Nam**, Paju-si (KR)(51) **Int. Cl.****H10K 59/80** (2006.01)**H10K 59/131** (2006.01)(52) **U.S. Cl.**CPC ..... **H10K 59/878** (2023.02); **H10K 59/131**  
(2023.02); **H10K 59/351** (2023.02)(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)(21) Appl. No.: **18/397,456**(22) Filed: **Dec. 27, 2023**(30) **Foreign Application Priority Data**

Dec. 27, 2022 (KR) ..... 10-2022-0185346

Dec. 19, 2023 (KR) ..... 10-2023-0186100

(57)

**ABSTRACT**

A display apparatus is discussed, which can improve light extraction efficiency of light emitted from a light emitting element layer. In one example, the display apparatus includes a substrate having a plurality of pixels with a plurality of subpixels, a pattern portion disposed on the substrate and formed to be concave between the plurality of subpixels, a reflective portion on the pattern portion, and a plurality of lines for driving the plurality of subpixels. The plurality of subpixels include a light emission area and a non-light emission area adjacent to the light emission area, and the plurality of lines are disposed in the non-light emission area. Further, the pattern portion is provided to surround the light emission area, and at least one of the plurality of lines partially overlaps the pattern portion.

