

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231191 A1 Wang et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) ELECTROLYTE AND ELECTROCHEMICAL DEVICE THEREOF AND ELECTRONIC DEVICE

- (71) Applicants: Envision Dynamics Technology (Jiangsu) Co., Ltd., Jiangsu (CN); **Envision Intelligent Innovation** Dynamics Technology (Shanghai) Ltd., Shanghai (CN)
- (72) Inventors: Renhe Wang, Shanghai (CN); Ziyuan Wang, Shanghai (CN); Le Yu, Shanghai (CN)
- (73) Assignees: Envision Dynamics Technology (Jiangsu) Co., Ltd., Jiangsu (CN); **Envision Intelligent Innovation** Dynamics Technology (Shanghai) Ltd., Shanghai (CN)
- (21) Appl. No.: 18/009,991
- (22) PCT Filed: May 27, 2022
- (86) PCT No.: PCT/CN2022/095586 § 371 (c)(1),

Dec. 13, 2022 (2) Date:

(30)Foreign Application Priority Data

May 28, 2021 (CN) 202110592885.9

Publication Classification

(51)	Int. Cl.	
	H01M 10/0566	(2006.01)
	H01M 4/36	(2006.01)
	H01M 4/587	(2006.01)
	H01M 4/505	(2006.01)

H01M 4/525 (2006.01)H01M 10/0525 (2006.01)(2006.01)H01M 4/58

(52) U.S. Cl.

CPC H01M 10/0566 (2013.01); H01M 4/364 (2013.01); H01M 4/587 (2013.01); H01M 4/505 (2013.01); H01M 4/525 (2013.01); H01M 10/0525 (2013.01); H01M 4/5825 (2013.01); H01M 2004/027 (2013.01)

(57)ABSTRACT

The disclosure discloses an electrolyte and an electrochemical device thereof, and an electronic device. The electrolyte includes a compound represented by formula (I):

wherein R₁, R₃, and R₄ are each independently selected from hydrogen, a cyano group, a substituted or unsubstituted C₁₋₁₂ hydrocarbon group, a substituted or unsubstituted C_{1-12} carboxy group, a substituted or unsubstituted C_{6-26} aryl group, a substituted or unsubstituted C_{2-12} amide group, a substituted or unsubstituted C₀₋₁₂ phosphate group, a substituted or unsubstituted C₀₋₁₂ sulfonyl group, a substituted or unsubstituted C₀₋₁₂ siloxy group or a substituted or unsubstituted C₀₋₁₂ boronate group, when being substituted, a substituent includes a halogen atom. The electrolyte of the disclosure may improve the high-temperature cycle performance and room-temperature cycle performance while reducing the internal resistance of the electrochemical