

# (19) United States

# (12) Patent Application Publication (10) Pub. No.: US 2024/0213014 A1 Kuhlbusch et al.

### Jun. 27, 2024 (43) **Pub. Date:**

### (54) SYSTEM AND METHOD FOR DELIVERY OF AN ANALYTE AND A REFERENCE

(71) Applicant: Thermo Fisher Scientific (Bremen)

GmbH, Bremen (DE)

Inventors: Nils Kuhlbusch, Bremen (DE); Dieter

Juchelka, Bremen (DE); Andreas

Hilkert, Bremen (DE)

(73) Assignee: Thermo Fisher Scientific (Bremen)

GmbH, Bremen (DE)

- (21) Appl. No.: 18/545,900
- (22) Filed: Dec. 19, 2023
- (30)Foreign Application Priority Data

Dec. 22, 2022 (GB) ...... 2219580.4

#### **Publication Classification**

(51) Int. Cl. H01J 49/42 (2006.01) (52) U.S. Cl. CPC ...... H01J 49/42 (2013.01)

#### ABSTRACT (57)

The present invention relates to an apparatus for isotope ratio mass spectrometry that comprises: a mass spectrometer comprising a sample input and a system for delivery of an analyte and a reference substance to the mass spectrometer. The system comprising: a switchable multi-way valve, comprising an analyte sample inlet, a reference sample inlet and a delivery outlet, wherein the analyte sample inlet is arranged to receive an analyte sample comprising the analyte, the reference sample inlet is arranged to receive a reference sample comprising the reference substance, and the delivery outlet is configured for passage of the analyte sample or the reference sample out of the multi-way valve to the sample input of the mass spectrometer; a first means, for regulating a supply of the reference sample to the reference sample inlet; and a second means, for regulating a supply of the analyte sample to the analyte sample inlet; wherein the multi-way valve is switchable between a first position and a second position, wherein in the first position, the reference sample inlet is connected to the delivery outlet, for passage of the reference sample through the multi-way valve and to the sample input of the mass spectrometer; and in the second position, the analyte sample inlet is connected to the delivery outlet, for passage of the analyte sample through the multi-way valve and to the sample input of the mass spectrometer. The present invention also relates to a method for isotope ratio mass spectrometry.

