

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0361327 A1 CHANG et al.

Nov. 10, 2022 (43) **Pub. Date:**

(54) SENSOR LENS ASSEMBLY HAVING NON-REFLOW CONFIGURATION

(71) Applicant: KINGPAK TECHNOLOGY INC.,

Hsin-Chu County (TW)

Inventors: CHIA-SHUAI CHANG, Hsin-Chu

County (TW); CHIEN-CHEN LEE, Hsin-Chu County (TW); JUI-HUNG HSU, Hsin-Chu County (TW)

(21) Appl. No.: 17/667,486

(22) Filed: Feb. 8, 2022

Related U.S. Application Data

(60) Provisional application No. 63/184,622, filed on May 5, 2021.

(30)Foreign Application Priority Data

Nov. 12, 2021 (TW) 110142150

Publication Classification

(51) Int. Cl.

H05K 1/11 (2006.01)G02B 7/02 (2006.01) G02B 7/00 (2006.01)H05K 1/02 (2006.01)

(52) U.S. Cl.

CPC H05K 1/111 (2013.01); G02B 7/02 (2013.01); G02B 7/006 (2013.01); H05K 1/0274 (2013.01); H05K 2201/10151 (2013.01); H05K 2201/09409 (2013.01); H05K 2201/10121 (2013.01); H05K 2201/09445 (2013.01)

(57)ABSTRACT

A sensor lens assembly having a non-reflow configuration is provided. The sensor lens assembly includes a circuit board, an electronic chip assembled to the circuit board, a sensor chip, a die attach film (DAF) pre-bonded onto the sensor chip, a plurality of wires electrically coupling the electronic chip and the sensor chip to the circuit board, a supporting adhesive layer, a light-permeable sheet, and an optical module that is fixed to the circuit board for surrounding the above components. The sensor chip is adhered to the electronic chip through the DAF such that a sensing region of the sensor chip is perpendicular to a central axis of the optical module. The supporting adhesive layer is in a ringed shape and is disposed on a top surface of the sensor chip. The light-permeable sheet is disposed on the supporting adhesive layer and faces the sensor chip.

