US 20240237388A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0237388 A1**

Lu et al. (43) **Pub. Date: Jul. 11, 2024**

(54) **LIGHT EMITTING DEVICE AND PRODUCING METHOD THEREOF, AND DISPLAY DEVICE**

(71) Applicants: **Beijing BOE Technology Development Co., Ltd.**, Beijing (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

(72) Inventors: **Zhigao Lu**, Beijing (CN); **Haowei Wang**, Beijing (CN); **Xiaoyuan Zhang**, Beijing (CN); **Zhuo Chen**, Beijing (CN)

(73) Assignees: **Beijing BOE Technology Development Co., Ltd.**, Beijing (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

(21) Appl. No.: **17/922,821**

(22) PCT Filed: **Dec. 29, 2021**

(86) PCT No.: **PCT/CN2021/142481**

§ 371 (c)(1),
(2) Date: **Nov. 2, 2022**

Publication Classification

(51) **Int. Cl.**

H10K 50/16	(2006.01)
H10K 50/115	(2006.01)
H10K 71/20	(2006.01)
H10K 101/30	(2006.01)
H10K 102/00	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 50/166*** (2023.02); ***H10K 50/115*** (2023.02); ***H10K 71/233*** (2023.02); *H10K 2101/30* (2023.02); *H10K 2102/351* (2023.02)

(57) **ABSTRACT**

The present application provides a light emitting device and a producing method thereof, and a display device, which relates to the technical field of displaying, and may solve the problem of quantum-dot remaining. A light emitting device, wherein the light emitting device includes: a plurality of light emitting areas that are arranged in an array, and non-light emitting areas between neighboring light emitting areas; each of the light emitting areas includes an inorganic electron transporting layer, an organic electron transporting layer and a quantum-dot layer that are arranged sequentially in layer configuration; and an absolute value of a difference between an energy value of a lowest unoccupied molecular orbital of the inorganic electron transporting layer and an energy value of a lowest unoccupied molecular orbital of the organic electron transporting layer is less than or equal to a preset value.