US 20240213411A1

(19) **United States**

(12) **Patent Application Publication**

IM et al.

(10) **Pub. No.: US 2024/0213411 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si (KR)

(72) Inventors: **Hyun Deok IM**, Yongin-si (KR); **Buem Joon KIM**, Yongin-si (KR); **Won Ho LEE**, Yongin-si (KR)

(73) Assignee: **Samsung Display Co., LTD.**, Yongin-si (KR)

(21) Appl. No.: **18/500,226**

(22) Filed: **Nov. 2, 2023**

(30) **Foreign Application Priority Data**

Dec. 22, 2022 (KR) 10-2022-0182315

Publication Classification

(51) **Int. Cl.**

H01L 33/38	(2006.01)
G09G 3/32	(2006.01)
H01L 25/16	(2006.01)

(52) **U.S. Cl.**

CPC ***H01L 33/385*** (2013.01); ***G09G 3/32*** (2013.01); ***H01L 25/167*** (2013.01); *G09G 2300/0819* (2013.01); *G09G 2300/0842* (2013.01); *G09G 2300/0861* (2013.01)

(57) **ABSTRACT**

A display device includes: a first light emitting element disposed in a first light emitting area; a second light emitting element disposed in a second light emitting area; a first contact electrode electrically connected to a first end portion of the first light emitting element; a second contact electrode electrically connected to a second end portion of the first light emitting element; a third contact electrode electrically connected to a first end portion of the second light emitting element; and a connection electrode electrically connected to the second contact electrode and bypassing the first contact electrode to be electrically connected to the third contact electrode.