

(19) **United States**

(12) **Patent Application Publication**
SANO et al.

(10) **Pub. No.: US 2022/0393646 A1**

(43) **Pub. Date: Dec. 8, 2022**

(54) **RADIO FREQUENCY CIRCUIT,
COMMUNICATION DEVICE, AND ANTENNA
MODULE**

Publication Classification

(51) **Int. Cl.**
H03F 1/02 (2006.01)
H03F 3/21 (2006.01)
H04B 1/00 (2006.01)
H04B 1/04 (2006.01)
(52) **U.S. Cl.**
CPC H03F 1/0211 (2013.01); H03F 3/21
(2013.01); H04B 1/006 (2013.01); H04B 1/04
(2013.01); H03F 2200/171 (2013.01); H03F
2200/451 (2013.01); H03F 2200/111
(2013.01); H03F 1/0277 (2013.01)

(71) Applicant: **MURATA MANUFACTURING CO.,
LTD.**, Kyoto (JP)

(72) Inventors: **Tomohiro SANO**, Nagaokakyo-shi (JP);
Hirotsugu MORI, Nagaokakyo-shi (JP)

(21) Appl. No.: **17/820,652**

(22) Filed: **Aug. 18, 2022**

Related U.S. Application Data

(63) Continuation of application No. 16/897,481, filed on
Jun. 10, 2020, now Pat. No. 11,469,712.

Foreign Application Priority Data

Jun. 13, 2019 (JP) 2019-110218

ABSTRACT

A radio frequency circuit includes a power amplifier configured to selectively amplify one of a first radio frequency signal and a second radio frequency signal that have different bandwidths, and when the first radio frequency signal is input to the power amplifier, a first bias signal is applied to the power amplifier, and when the second radio frequency signal is input to the power amplifier, a second bias signal different from the first bias signal is applied to the power amplifier.

