

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0179976 A1

May 30, 2024 (43) **Pub. Date:**

(54) **DISPLAY DEVICE**

(71) Applicant: SAMSUNG DISPLAY CO., LTD.,

YONGIN-SI (KR)

(72) Inventors: BYUNG SUN KIM, YONGIN-SI

(KR); SUN JA KWON, YONGIN-SI (KR); YANG WAN KIM, YONGIN-SI (KR); HYUN AE PARK, YONGIN-SI (KR): SU JIN LEE, YONGIN-SI (KR): JAE YONG LEE, YONGIN-SI (KR)

(21) Appl. No.: 18/434,297

(22) Filed: Feb. 6, 2024

Related U.S. Application Data

Continuation of application No. 17/137,742, filed on Dec. 30, 2020, now Pat. No. 11,917,873, which is a continuation of application No. 15/453,794, filed on Mar. 8, 2017, now Pat. No. 10,886,354.

(30)Foreign Application Priority Data

May 19, 2016 (KR) 10-2016-0061638

Publication Classification

(51) Int. Cl. H10K 59/131 (2006.01)G09G 3/3233 (2006.01)H10K 59/124 (2006.01)

U.S. Cl.

H10K 59/131 (2023.02); G09G 3/3233 CPC (2013.01); H10K 59/124 (2023.02); G09G 2300/043 (2013.01); G09G 2300/0809 (2013.01); G09G 2300/0819 (2013.01); G09G 2300/0842 (2013.01); G09G 2300/0861 (2013.01); G09G 2310/0291 (2013.01)

(57)**ABSTRACT**

A display device includes a substrate having a pixel area and a peripheral area, a plurality of pixels disposed on the substrate in the pixel area, a plurality of data lines that supply a plurality of data signals to the pixels, a plurality of scan lines that supply a plurality of scan signals to the pixels, a plurality of power supply lines that supply a first voltage to the pixels, and first through third insulating layers. The first insulating layer is disposed on the substrate, the second insulating layer is disposed on the first insulating layer, and the third insulating layer is disposed on the second insulating layer. The scan lines are disposed below the third insulating layer on the substrate in the pixel area, and are disposed on the third insulating layer in the peripheral area.

